

# Vector™ V500 Smart Antenna

## Multi-Frequency, Multi-GNSS Vector Compass



key features

- Simple all-in-one RTK-capable
- Multi-frequency GPS/GLONASS/BeiDou/Galileo/QZSS/IRNSS
- Athena™ RTK and Atlas® L-band capable
- Fully rugged solution for the harshest environments

---

The Vector V500 is Hemisphere GNSS' all-in-one multi-frequency, multi-GNSS smart antenna which provides RTK-level position and precise heading. This rugged design is sealed for the harshest environments and is a great solution for professional marine and other challenging applications.

The all-in-one V500 combines simple installation with consistent and precise heading accuracy and RTK positioning.



Precision@HGNS.com  
www.HGNS.com

# Vector V500 Smart Antenna

## GNSS Receiver Specifications

Receiver Type:	Vector GNSS RTK Receiver
Signals Received:	GPS, GLONASS, BeiDou, Galileo, QZSS <sup>7</sup> , IRNSS <sup>7</sup> , and Atlas <sup>6</sup>
Channels:	744
GPS Sensitivity:	-142 dBm
SBAS Tracking:	3-channel, parallel tracking
Update Rate:	10 Hz standard, 50 Hz optional
Timing (1PPS) Accuracy:	20 ns
Rate of Turn:	100°/s maximum
Cold Start:	40 s (no almanac or RTC)
Warm Start:	20 s typical (almanac and RTC)
Hot Start:	5 s typical (almanac, RTC and position)
Heading Fix:	10 s typical (Hot Start)
Antenna Input Impedance:	50 Ω
Maximum Speed:	1,850 mph (999 kts)
Maximum Altitude:	18,288 m (60,000 ft)
Differential Options:	SBAS, Atlas (L-band), RTK

## Accuracy

Positioning:	Horizontal (95%)	Vertical (95%)
Autonomous, no SA <sup>2</sup> :	2.4 m	
SBAS (WAAS) <sup>2</sup> :	0.6 m	
Atlas H10 (L-band) <sup>6</sup> :	0.08 m	
Atlas H30 (L-band) <sup>6</sup> :	0.3 m	
Atlas Basic (L-band) <sup>6</sup> :	0.5 m	
RTK <sup>1</sup> :	8 mm + 1 ppm	15 mm + 2 ppm
Heading (RMS):	< 0.2°	
Pitch/Roll (RMS):	1°	
Heave (RMS):	30 cm (DGPS) <sup>6</sup> , 10 cm (RTK) <sup>6</sup>	

## L-Band Receiver Specifications

Channels:	1525 to 1560 MHz
Sensitivity:	-130 dBm
Channel Spacing:	5 kHz
Satellite Selection:	Manual or Automatic
Reacquisition Time:	15 sec (typical)
Processor:	DSP for demodulation and protocol decoding module provides processing for the differential algorithms

## Communications

Ports:	1x full-duplex RS-232/RS-422, 1x RS232, 2x CAN, 1x Ethernet
Baud Rates:	4800 - 115200
Radio Interfaces:	Bluetooth 2.0 (Class 2), Wi-Fi 2.4 GHz
Correction I/O Protocol:	Atlas, Hemisphere GNSS proprietary, RTCM v2.3 (DGPS), RTCM v3 (RTK), CMR, CMR+ <sup>1</sup>
Data I/O Protocol:	NMEA 0183, Hemisphere GNSS binary
Timing Output:	1PPS, CMOS, active low, falling edge sync, 10 kΩ, 10 pF load
Event Marker Input:	CMOS, active low, falling edge sync, 10 kΩ, 10 pF load
Heading Warning I/O:	Open relay system indicates invalid heading

## Power

Input Voltage:	9 - 36 VDC with reverse polarity operation
Power Consumption:	TBD
Current Consumption:	TBD
Reverse Polarity Protection:	Yes

## Environmental

Operating Temperature:	-40°C to +70°C (-40°F to +158°F)
Storage Temperature:	-40°C to +85°C (-40°F to +185°F)
Humidity:	95% non-condensing
Vibration:	IEC60945 Section 8.7 IEC60945
EMC:	FCC part 15 Subpart B, CISPR32
IMO Wheelmark Certification:	No
Enclosure:	IP69

## Mechanical

Dimensions:	66.3L x 20.9 W x 14.6 H cm
Weight:	2.1kg
Status Indications (LED):	Power, GNSS Lock, Heading
Power/Data Connector:	22 pin environmentally sealed

## Aiding Devices

Gyro:	Provides smooth heading, fast heading reacquisition and reliable < 0.5° per min heading for periods up to 3 min. when loss of GPS has occurred <sup>4</sup>
Tilt Sensors:	Provide pitch, roll data and assist in fast start-up and reacquisition of heading solution

1 Depends on multipath environment, number of satellites in view, satellite geometry, no SA, and ionospheric activity

2 Depends on multipath environment, number of satellites in view, WAAS coverage and satellite geometry

3 Depends on multipath environment, number of satellites in view, satellite geometry, baseline length (for differential services), and ionospheric activity

4 Based on a 40 second time constant

5 Hemisphere GNSS proprietary

6 Requires a Hemisphere GNSS subscription

7 With future firmware upgrade and activation

## Authorized Distributor:



Copyright Hemisphere GNSS, Inc. All rights reserved. Specifications subject to change without notice.  
Hemisphere GNSS, Athena, Atlas, and Vector are trademarks of Hemisphere GNSS, Inc.  
Rev. 07/18



Hemisphere GNSS, Inc.  
8515 E. Anderson Drive  
Scottsdale, AZ, USA 85255

Toll-Free: +1 (855) 203-1770  
Phone: +1 (480) 348-6380  
Fax: +1 (480) 270-5070  
Precision@HGNSS.com  
www.HGNSS.com